

Truck Loading Unloading Conveyor

CBLC600 / CBLC800



PRODUCTS DETAILS



Flexible conveyor with independent control box



End slave section height is adjustable by hand wheel



With hydraulic power unit for height adjustment



7.2m flexible powered roller conveyor



Flexible conveyor Supporting Bracket



Truck Loading Conveyor Main Frame



Coated Roller For Bags, Using Rubber

DATASHEET

Inclined Belt Conveyor

Models	CBLC600 / CBLC800
Conveyor Belt Width	600mm or 800mm
Conveyor Belt Type	3mm PVC Belt (anti-skidding)
Load-in Height	1600 or 1800mm
Load-out Height	550-1050 or 850-1350
Adjustable Speed	10-20m/min
Load Capacity	50kg/m
Belt Driven Motor	1.5kw
Hydraulic Power Unit	1.5kw
Frequency Inverter	Delta or Others
Main Electric Elements	Schneider or Others
Heavy Duty Caster	Φ200mm lockable swivel PU casters
Frame Construction	carbon steel (painted in blue RAL 5015)
Power Supply	220V/50Hz single phase, 380V/50Hz three phase

Flexible Powered Roller Conveyor

Roller Conveyor Length (m)	2.8-7.2
Rollers	Φ50*T1.5 galvanized steel rollers, face length 600mm or 800
Roller Driven Belt	Poly V-belt
Motor Power	90W or 120w, 7 rollers / section
Adjustable Speed	10-18m/min, two way
Adjustable Height	600-800mm
Max. Load Capacity	50kg/m
Flexible Frame	272*5mm X shape side links, galvanized or painted black
Supporting Legs	32*32*2mm steel tubes, painted in black
Castors	5" high quality swivel PU casters with brakes
Voltage	220V/50Hz single phase, 380V/50Hz three phase
Control Panel	Forward/Stop/Reverse, Emergency Stop
Power Supply	220V/50Hz single phase, 380V/50Hz three phase

DRAWINGS (Standard for CBLC600)

